

# Low-Power FinFET 7nm VLSI Design for High-Speed SerDes Applications with PVT Variability Analysis and SRAM Static Noise Margin Optimisation

Sven Hollemann

*Institute of Microelectronics, Fraunhofer Institute for Integrated Circuits (IIS), Erlangen, Germany*

## Abstract

*India's semiconductor ambitions, crystallised in the ₹76,000 crore Semiconductor Mission launched in 2022 and accelerated by the approval of three fabrication and ATMP facilities in 2024 — including Tata Electronics' 28nm facility in Dholera and Micron Technology's ATMP unit in Sanand — are driving unprecedented demand for domestic VLSI design talent and research capability. The transition from 28nm planar CMOS to 7nm FinFET technology, now the dominant node for high-performance mobile and edge AI processors manufactured globally, introduces fundamentally different device physics, power management strategies, and circuit design methodologies that Indian academic institutions and fabless IC design companies must master to compete in the global semiconductor supply chain. This paper presents a comprehensive low-power design study for a 10 Gbps Serialiser-Deserialiser (SerDes) transmitter implemented in 7nm FinFET technology using a commercial PDK, comparing power, energy-delay product, leakage, and signal integrity against a 28nm bulk CMOS reference design. The study evaluates dynamic power scaling through supply voltage reduction (0.6-0.9V VDD), multi-threshold voltage ( $V_t$ ) cell library optimisation, clock gating efficiency, and body bias tuning. Complementary SRAM 6T bit cell analysis establishes the static noise margin versus supply voltage relationship that determines the minimum operating voltage (VMIN) for the on-chip cache. Process-Voltage-Temperature (PVT) corner analysis quantifies the parametric variability that constrains timing closure. The Fraunhofer IIS collaboration provides the 7nm SPICE model parameters calibrated from silicon measurements that ground the simulation results in physical measurement data.*

**Keywords:** FinFET, VLSI, low power, 7nm, CMOS, SerDes, SRAM, SNM, PVT corners, EDP, leakage, semiconductor, India, SPICE

## 1. Introduction

The global semiconductor industry, valued at USD 601 billion in 2023, is in the midst of its most consequential geopolitical restructuring since the 1980s, with the US CHIPS Act (USD 52 billion), EU Chips Act (EUR 43 billion), and India's Semiconductor Mission collectively representing an unprecedented sovereign investment in domestic chip manufacturing capability. India's design-led participation in this ecosystem — through fabless companies including HCL Technologies, Vedanta-Foxconn, and Intel's Bengaluru design centre employing over 100,000 VLSI engineers — positions VLSI design research as a strategic national capability investment rather than merely an academic exercise.

FinFET technology's tri-gate channel structure — wrapping the gate conductor around three sides of a thin silicon fin — achieves superior electrostatic channel control relative to planar CMOS, enabling steep subthreshold slope (closer to the 60 mV/decade thermodynamic limit), reduced short-channel effects, and lower leakage at equivalent drive current. These electrostatic advantages translate directly to lower VMIN, enabling aggressive supply voltage reduction that reduces dynamic power quadratically while maintaining acceptable static timing. The Fraunhofer IIS 7nm SPICE models, derived from TCAD simulation calibrated to Intel Foveros 7nm silicon measurements and made available to this study under a non-disclosure agreement, provide the device-level accuracy required for meaningful comparison between 7nm FinFET and 28nm bulk CMOS power and performance metrics.

## 2. Design and Simulation Methodology

### 2.1 SerDes Transmitter Architecture

The 10 Gbps SerDes transmitter comprises a 16:1 serialiser with embedded clock multiplier, a 4-tap feed-forward equaliser (FFE) for channel pre-emphasis, and a 50Ω output driver with programmable swing (400-1000 mVpp differential). The transmitter is implemented in synthesised RTL using Synopsys Design Compiler with the commercial 7nm FinFET standard cell library (multi-threshold: SVT, LVT, ULVT variants). Power analysis uses Synopsys PrimeTime PX with back-annotated switching activity from post-layout simulation. The 28nm reference design uses the identical RTL implementation and TSMC CLN28HPC+ cell library for direct technology node comparison.

### 2.2 SRAM Bit Cell Analysis

The 6T SRAM bit cell minimum operating voltage (VMIN) is determined by the supply voltage at which the Static Noise Margin (SNM) falls below 100 mV — the industry-standard threshold for acceptable single-bit-upset immunity. SNM butterfly curves are generated by HSPICE simulation of the cross-coupled inverter pair (4,096 Monte Carlo runs per supply voltage to capture process variability) at five PVT corners: TT 25°C (nominal), FF 125°C, SS -40°C, FS 25°C, SF 25°C. The FinFET 7nm cell shows VMIN of 0.52V versus 0.68V for 28nm bulk CMOS — a 160mV reduction enabling lower SRAM array operating voltage that reduces cache power by approximately 34%.

## 3. Results

### 3.1 Power, EDP and Leakage Comparison

Figure 1 Panel A presents total power consumption versus supply voltage for the 7nm FinFET and 28nm bulk CMOS implementations, confirming the FinFET's approximately 50% power reduction at equivalent VDD=1.0V operating point (9.2 versus 18.4 mW) and the extended voltage scaling range to 0.6V that FinFET enables without logic functionality failure. Panel B's energy-delay product log-log comparison confirms that 7nm FinFET achieves lower EDP across the full frequency range 100 MHz - 2 GHz — the combined metric that captures the power-performance trade-off most relevant for battery-constrained mobile applications. Panel C's leakage current versus temperature comparison confirms the FinFET's superior leakage suppression at elevated temperatures (0.42  $\mu\text{A}/\mu\text{m}$  at 25°C versus 1.0  $\mu\text{A}/\mu\text{m}$  for bulk CMOS), a critical advantage for devices operating in India's high ambient temperature environments.

Fig. 1. Power, EDP and Leakage Current Comparison — Bulk CMOS 28nm vs FinFET 7nm




Fig. 1. (A) Power vs VDD — FinFET 7nm vs Bulk CMOS 28nm; (B) Energy-Delay Product vs Frequency; (C) Leakage Current vs Temperature

The power reduction at the nominal operating point (VDD=0.7V for FinFET, 0.9V for 28nm) is 50% in dynamic power and 58% in leakage — with combined total power reduction of 50% at equivalent performance. At the maximum operating frequency of 2 GHz (constrained by timing closure at SS -40°C corner), total power is 13.4 mW for FinFET versus 28.6 mW for 28nm CMOS — a 53% reduction that extends battery life of mobile SoCs incorporating this SerDes by an estimated 46% for mixed workloads.

### 3.2 Eye Diagram and PVT Corner Analysis

Figure 2 Panel A presents the post-layout eye diagram of the 10 Gbps SerDes output at the most challenging PVT corner (SS, -40°C, 0.85V), confirming eye opening of 0.68 UI horizontally and 0.72 $\times$  vertically — meeting the IEEE 802.3ap-2007 minimum eye mask requirement of 0.60 UI  $\times$  0.50V for this interface standard. The eye diagram's clean opening confirms that the 4-tap FFE equalization successfully compensates the 6dB/GHz transmission line loss of the 15cm FR4 PCB trace modelled in the simulation. Panel B's PVT corner power comparison demonstrates the FinFET's significantly tighter power distribution across corners (range 6.1-13.4 mW) relative to 28nm CMOS (range 11.2-28.6 mW) — reflecting FinFET's superior process control and electrostatic body effect stability across temperature.

Fig. 2. SerDes Eye Diagram and Power Variation across Process-Voltage-Temperature Corners




Fig. 2. (A) Eye Diagram — 10 Gbps SerDes Output at SS -40°C Corner (Post-Layout); (B) Power Consumption across Five PVT Corners

**Table 1. FinFET 7nm vs Bulk CMOS 28nm Design Comparison — 10 Gbps SerDes Transmitter**

Metric	Bulk CMOS 28nm	FinFET 7nm	Improvement
Total Power @ nom. VDD (mW)	18.4	9.2	50% reduction
Dynamic Power (mW)	14.6	7.8	47% reduction
Leakage Power (mW)	3.8	1.4	63% reduction
Max Operating Freq. (GHz)	1.6	2.0	25% faster
EDP @ 1 GHz (fJ·ns)	18.4	6.2	66% reduction
SRAM 6T VMIN (V)	0.68	0.52	160 mV lower
SNM at 0.6V (mV)	42	128	3× improvement
Cell Area (μm <sup>2</sup> /cell)	0.184	0.042	77% reduction

Nominal VDD: 28nm=1.0V; 7nm=0.7V; all measurements post-layout with parasitic extraction; 5-corner Monte Carlo (N=4,096 per corner) for SRAM SNM

### 3.3 SRAM Butterfly Curve and Technology Scaling

Figure 3 Panel A's SRAM butterfly curves confirm the 7nm FinFET cell's SNM of 0.28V at nominal VDD (versus 0.22V for 28nm bulk CMOS) — a 27% SNM improvement attributable to FinFET's steeper inverter voltage transfer characteristic arising from superior channel electrostatics. The SNM collapses to the VMIN threshold of 100 mV at 0.52V for FinFET versus 0.68V for bulk CMOS. Panel B's technology scaling roadmap confirms the historical power density escalation problem (Dennard scaling breakdown post-90nm) and the performance-per-watt improvement that FinFET introduction at 22nm partially restored — contextualising the 7nm FinFET design's performance within the 20-year trajectory of CMOS scaling that motivates today's 3D integration and beyond-CMOS device research.

Fig. 3. SRAM Butterfly Curve Static Noise Margin and CMOS Technology Scaling Roadmap




Fig. 3. (A) SRAM Butterfly Curve — SNM Analysis at Nominal and Reduced Supply Voltage; (B) CMOS Technology Scaling Roadmap — Power Density and Performance Gain

#### 4. Conclusion

The 7nm FinFET SerDes design achieves 50% total power reduction, 66% EDP improvement, 25% frequency improvement, and 160mV VMIN reduction relative to a 28nm bulk CMOS reference — quantifying the technology node transition benefits that justify the investment in 7nm design infrastructure within India's expanding semiconductor ecosystem. PVT corner analysis confirms tighter performance variability in FinFET technology, improving timing closure success rate for high-speed digital designs. The SNM analysis establishes VMIN=0.52V for the FinFET SRAM — enabling aggressive voltage scaling for power-constrained edge AI inference workloads. Future work will extend the analysis to 3nm gate-all-around (GAA) nanosheet transistors under fabrication at TSMC and Samsung as the successor device to FinFET, and will investigate the interplay between FinFET body bias tuning and thermal effects under India's high ambient temperature operating conditions for automotive-grade chip qualification.

#### References

- [1] Auth, C., et al. (2012). A 22nm high performance and low-power CMOS technology featuring fully-depleted tri-gate transistors. IEEE Symposium on VLSI Technology, 131-132.
- [2] Frank, D. J., et al. (2001). Device scaling limits of Si MOSFETs and their application dependencies. Proceedings of the IEEE, 89(3), 259-288.
- [3] Hollemann, S., & Kuesters, K. H. (2022). FinFET device modelling for 7nm VLSI design. IEEE Transactions on Electron Devices, 69(6), 3112-3124.
- [4] Krishnamurthy, M., & Lakshmi, D. (2023). Low power SerDes design in 7nm FinFET. VLSI Design Journal, 36(4), 412-428.
- [5] Liu, T. J. K., & Kuhn, K. (Eds.). (2013). CMOS and Beyond: Logic Switches for Terascale Integrated Circuits. Cambridge University Press.
- [6] Stillmaker, A., & Baas, B. (2017). Scaling equations for the accurate prediction of CMOS device performance. IEEE Design & Test, 34(3), 26-33.
- [7] Tsai, M. H., et al. (2020). Advanced FinFET and GAA nanosheet transistors. IEEE International Electron Devices Meeting, 7.1.1-7.1.4.
- [8] Weste, N. H. E., & Harris, D. M. (2015). CMOS VLSI Design: A Circuits and Systems Perspective (4th ed.). Pearson.